



## Certification Record

CUSTOMER	CLASS	FILE
Draka Elevator Products, Inc. 2151 North Church St, Rocky Mount NC 27804 USA	<u>5831-01</u> WIRES-Flexible Cord	030361_0_000

**Refer to Class Description for program details**

TO THE REQUIREMENTS OF CSA STANDARD C22.2 NO. 49-10:

- ETT, multi-conductor round construction rated 60C, 300V, FT1. Insulation: PVC, in all colours except clear and translucent. Outer braid. Coaxial cable: optional. Jacket: PVC, in all colours except clear and translucent. Size range: 20 to 12 AWG. Number of conductors: 2 or more.
- ETT, multi-conductor round construction rated 60C, 600V, FT1. Insulation: PVC, in all colours except clear and translucent. Outer braid. Coaxial cable: optional. Jacket: PVC, in all colours except clear and translucent. Size range: 12 to 2 AWG. Number of conductors: 2 or more.
- ETP, multi-conductor flat parallel construction rated 60C, 300V, FT1. Insulation: PVC, in all colours except clear and translucent. Coaxial cable: optional. Jacket: PVC, in all colours except clear and translucent. Size range: 20 to 12 AWG. Number of conductors: 2 or more.
- ETP, multi-conductor flat parallel construction rated 60C, 600V, FT1. Insulation: PVC, in all colours except clear and translucent. Coaxial cable: optional. Jacket: PVC, in all colours except clear and translucent. Size range: 12 to 2 AWG. Number of conductors: 2 or more.
- Hoistway cable, multi-conductor round construction rated 60/90C, 300V, FT1. Insulation: PVC, in all colours except clear and translucent. Jacket: optional, PVC, in all colours except clear and translucent. Size range: 20 to 12 AWG. Number of conductors: 2 to 75.
- Hoistway cable, multi-conductor round construction rated 60/90C, 600V, FT1. Insulation: PVC, in all colours except clear and translucent. Jacket: optional, PVC, in all colours except clear and translucent. Size range: 18 to 12 AWG. Number of conductors: 2 to 75.

/dlg

Copyright © 2013 CSA International. All rights reserved.